# Bently Nevada 330303-006-20-90-00-00 Manual

| | |
|---|---|
| Brand | Bently Nevada |
| Product Series | Sheet32 |
| Product Type | 3300 XL High Temperature Probe, Smooth Case |

## Description

Manufacturer : Bently Nevada

Product No. : 330303-006-20-90-00-00

Product type : 3300 XL High Temperature Probe, Smooth Case

Made in U.S.A

Overall Case Length: 006 = 0.6 in

Hardline Length Option : 20= 2.0 metres (6.6 feet)

Total Length Option: Note: Extension cable is included with the proximity probe. : 90 = 9.0 metres (30 feet)

Extension Cable Armor Option: 00 = Without stainless steel
armor

Agency Approval Option : 00 = Not required

Probe dc Resistance
Probe Length (m) 2.0
Resistance from the Center Conductor to the Outer Conductor (RpROBE) (°hms) 5.82

Incremental Scale
Factor (ISF)
3.94 V/mm (100
mV/mil) ±9.65%
including
interchangeability
error when measured
in increments of 0.5
mm (20 mils) over the
4.0 mm (160 mil) linear
range.
Deviation from best fit
straight line (DSL)
Less than ±78 |xm
(±3.1 mils).

System performance over extended temperatures
Over a probe temperature range of 22oCto+350°C (72oFto+662oF) the ISF remains within ±30% of 3.94 V/mm (100 mV/mil), the DSL remains within ±0.51 mm (±20 mils).
Frequency Response
0 to 6 kHz: +0, -3 dB typical, with up to 305 metres (1000 feet) of field wiring.
Recommended Minimum Target Size
30.5 mm (1.2 in) diameter (flat target)
Recommended Minimum Shaft Diameter
152 mm (6.0 in)

Probe Tip Material Ceramic
Probe Case Material AISI 316L stainless steel (SST).

Probe
117 g/m (1.26 oz/ft) of hardline cable + 12 g/cm (1.07 oz/in) of case

Operating and Storage Temperature
-34°C to+350°C (-30°F to +662°F)