Bently Nevada 330854-080-25-00 Manual

Brand	Bently Nevada
Product Series	330850&330854
Product Type	-

Description

Manufacturer : Bently Nevada

Part Number : 330854-080-25-00

3300 XL 25 mm Extension Cable

330854-AXXX-BXX-CXX

A: Cable Length Option : 0 8 0 = 8.0 metres (26.2 feet)

B: Armor and Cable Option : 25 = Armored High Temperature FluidLoc cable

C: Agency Approval Option : 0 0 =No Approvals

Weight : 45 g/m (0.5 oz/ft)

Make sure that the extension cable length and the probe length, when added together, equal the Proximitor Sensor total length.

Each probe and cable are provided with connector protectors and a disposable connector protector installation tool to ensure that the connectors remain free of contamination. The ClickLoc connector on the probe lead has a removable collar that facilitates routing the cable through tight clearances.

Extension Cable dc Resistance
Length of Extension Cable (m) 8.0
Resistance from Center Conductor to Center Conductor (RCORE) (ohms) 2.0 ± 0.5
Resistance from Coaxial Conductor to Coaxial Conductor (RJACKET) (ohms) 0.6 ± 0.2

Extension Cable Material
75 Ω triaxial, perfluoroalkoxyethylene

(PFA) insulated FluidLoc cable.

Extension Cable 45 g/m (0.5 oz/ft)
Armored Extension Cable 140 g/m (1.5 oz/ft)

Extension Cable Temperature Range
Operating
and Storage
Temperature
-35°C to +200°C (-31°F to +392°F)