

Bently Nevada Service Manual

2300/20-00

1. Description

Manufacturer : Bently Nevada

3. Product Information

Manufacturer : Bently Nevada

Product No. : 2300/20-00

Product type : Vibration monitor

Made in U.S.A

Inputs

Power Input

DC Input 18~36 Vdc, max 7.5 W

Channel Types

ICP Accelerometers

Configurable

Bandpass filter

0.2 Hz to 20 kHz

Scale Factor

range

5 to 1000 mV/g

Full scale range 2 to 80 g peak

Current Sink

Source

3.3 mA $\pm$ 5%

Open Circuit

Voltage

-21 to -24 Vdc

Velocity

Configurable

Bandpass filter

0.2 Hz to 20 kHz

Scale Factor

range

5 to 1000 mV/in/s

Full scale range 0 to 50 in/s peak

Radial Vibration

Configurable

Bandpass filter

0.2 Hz to 20 kHz

Scale Factor

range

5 to 1000 mV/mil

Full scale range 0 to 160 mil peak-peak

Thrust Channel

Scale Factor

range

5 to 1000 mV/mil

Channel Types

Process Variable Channel

Support most of unit with default on

Temperature

Channel Hardware Specification

Configurable

Upper OK limit

-0.25 to -22 V (greater

than lower OK)

Configurable

Lower OK limit

-0.25 to -22 V (less than

upper OK)

Accuracy: $\pm$ 1% of full scale range

Independent 24-bit ADCs on input channels

Supports Bently transducer or 2/3 wires

custom transducer for Accelerometers,

Velomitor and Proximitor.

Speed/Keyphasor

Keyphasor transducers support multiple events per revolution and event ratios for speed inputs up to 20 kHz.

Threshold voltage

resolution

0.1 Vdc

Interfaces

Proximity Transducer Interface

Supply Voltage -22.8 to -25.2 Vdc

Maximum Rated

Current

15 mA

Short Circuit

Current

15.1 mA to 23.6 mA

Accuracy $\pm 1\%$ of full scale range

Input Impedance 3-wire Voltage Mode, 10 k Ω

RPM range 1 to 120,000

Proximity Switch Interface

Supply Voltage -10 to -24 Vdc

Interfaces

Lower Not Ok

limit

-2.75 ± 0.05 V

Rpm range 1 to 60,000

Other Inputs

Magnetic Pick up

Input voltage Adapt to sensor 284947

output

RPM range 200 to 120,000

Contact Inputs

Monitor

provides 3

contact

capabilities

with Input

terminals

Configuration lock

Latched alarm/relay reset

function

Monitor Bypass

Activate 0 to 10 k Ω

De-activate 150 k Ω to infinite

Button Inputs

External button to reset latched alarm and

relay

One buried

button

provides 3

functions

I Display monitor

information

I LCD contrast

adjustment

I Reset settings to default

Display Monitor Information

Reset listed

settings to

Default

I User account name

I IP Address

I FW/HW version

Jumper Between COM & Chassis GND

Jumpers are 2-pin terminal interfaces that connects COM to the Chassis ground (GND).

Alternatively, COM can be connected to an earth ground separately through a terminal.

Outputs

Buffered Output

Three buffered

outputs are available

on the monitor

through BNC

connectors

2 Vibration Outputs

1 Speed Output

Relays

Relays provide two

dry-contact outputs

May be normally

energized or

de-energized

No output feedback

determination

Relay Circuit Specification in

Non-Hazardous Area

Type Single pole, double

throw

Sealing Epoxy sealed

Contact life 100,000 cycles @ 5

amps

250 Vac

200,000 @ 1 amp, 24

Vdc

Insulationresistance 1000 MΩ minimum @

500 Vdc

Relay closed contact

resistance

1 Ω maximum

Relay open contact

resistance

1 MΩ minimum

Maximum switched

contact voltage

250 Vac / 250 Vdc

Maximum breaking

contact current

6 A @250 Vac / 6 A

@24 Vdc

Maximum switched

power

1500VA AC / 150 Watts

DC

Relay Circuit Specification in

Hazardous Area

Maximum

switched
contact
voltage and
current
6 A @24 Vac / 5 A @ 30 Vac /
5.8 A @24 Vdc / 4 A @30 Vdc
4-20mA Output (2300/20)
Two 4-20 mA outputs with internal current
loop power supply
4 to 20 mA output values are proportional to
the full-scale of the associated
measurement.
Software configuration may determine the
variable of each output. Voltage compliance:
0 to +12 Vdc range across load.
Load resistance: 0 to 600 Ω
Resolution: 0.3662 μ A
Accuracy: 1% over operating temperature
range
Update rate: 100 ms
Configurable with default 2 mA clamp current
No output feedback determination
Caution: Two 4-20 mA outputs will
NOT work with an external powered
loop.
Relay Circuit Specification in
Hazardous Area
LEDs
OK Indicates when the monitor is
operating properly.
Protection
fault
Indicates hardware fault that
is impacting alarm
determination.
User inhibit Indicates the alarm/relays
have been intentionally
inhibited from operation.
Bypass Indicates user initiated bypass
action.
Relay status Indicates if relays have been
activated.
TX/RX Indicates the Ethernet status
and monitor communicating
with remote software.
SPEED/AUX
channel
status
Indicates the speed channel
has valid speed signal input
OR operating correctly when
AUX.
Channel Alarm Status
Alert LED Engages if any channel is in
alert state.
Danger LED Engages if any channel is in
danger state.
LCD Display
Allows viewing machine speed, vibration

measurements value, setpoints, and configuration information.

Communications

Ethernet Ethernet, 10Base-T and

100Base-TX. Conforms to

IEEE802.3

RJ-45 for 10Base-T/100Base-TX

Ethernet cabling

Cable length: 100 meters (328 ft.)

maximum

Environmental Limits

Operating

Temperature

-30°C to +65°C

(-22°F to +149°F)

Storage

Temperature

-40°C to +85°C

(-40°F to +185°F)

Humidity Up to 95%, non-condensing

Vibration

Limitation

3 g

Battery Life for

Real Time

Clock

Powered: 38 years @ 50°C

(122°F)

Un-powered: 12 years @

50°C (122°F)

Trend Measurements:

Duration Intervals

Pre-Event Data 10 minutes 1 second

20 seconds 100

milliseconds

Post-Event Data 10 seconds 100

milliseconds

1 minute 1 second

Spectrums/Waveforms:

Duration Intervals

Pre-Event Data 2.5 minutes 10 seconds

Post-Event Data 1 minute 10 seconds

In the event of a network disruption

between the 2300 and System 1, the

2300 can store up to at least 5 alarm

data captures. (This requires System 1

Evolution 21.1 or newer and Firmware

release 3.2 or newer for 2300.)

Physical

Dimensions

(Width xDepth xHeight)

127 mm x 127 mm x 76.2 mm

(5 in. x 5 in. x 3 in.)

Weight 1.03 kg (2.26 lbs)

Mounting Panel mount or DIN rail

(adapter included)

2300/20-00: Monitor with 4-20 ma

Outputs

(including DIN rail mount assembly, manual

and monitor configuration software)

A: Approvals Option

00 =None

